

**UNCLASSIFIED**

**AD** **404 705**

**DEFENSE DOCUMENTATION CENTER**

**FOR**

**SCIENTIFIC AND TECHNICAL INFORMATION**

**CAMERON STATION, ALEXANDRIA, VIRGINIA**



**UNCLASSIFIED**

**NOTICE:** When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

CATALOGED BY AS11A  
1 100

1.3-3-5

TM-(L)-734/026/00

# TECHNICAL MEMORANDUM

(TM Series)

## DDC AVAILABILITY NOTICE

Qualified requesters may obtain  
copies of this report from DDC.

This document was produced by SDC in performance of contract AF 19(628)-1648, Space  
Systems Division Program, for Space Systems Division, AFSC.

1604 Simulation Program Descriptions Milestone 11	SYSTEM
Simulation Data Generation Control Routine (SDGC)	DEVELOPMENT
by	CORPORATION
G. A. Madrid	2500 COLORADO AVE.
15 March 1963	SANTA MONICA
Approved	CALIFORNIA
J. B. Munson	

The views, conclusions or recommendations expressed in this document do not necessarily reflect the official views or policies of agencies of the United States Government.

Permission to quote from this document or to reproduce it, wholly or in part, should be obtained in advance from the System Development Corporation.

Although this document contains no classified information it has not been cleared for open publication by the Department of Defense. Open publication, wholly or in part, is prohibited without the prior approval of the System Development Corporation.



MAY 24 1963

15 March 1963

- i -

TM-(L)-734/026/00

TABLE OF CONTENTS

	<u>Page</u>
1.0 IDENTIFICATION.....	1
2.0 PURPOSE.....	1
3.0 USAGE.....	1
3.1 Calling Sequence.....	1
3.2 Parameters.....	2
3.3 Error Printouts and Operator Action.....	2
3.4 Tape Assignments and Usage.....	3
3.5 Control Card Format.....	3
3.6 Input or Output Data.....	4
3.7 Key Settings.....	5
4.0 METHOD.....	5
5.0 RESTRICTIONS.....	6
5.1 Minimum Hardware or Machine Components Required.....	6
5.2 Subroutines Required.....	6
5.3 Limits on Input and Output Data.....	6
5.4 Reference Pool Items Set or Used.....	7
6.0 TIME REQUIREMENTS.....	7
7.0 STORAGE REQUIREMENTS.....	7
8.0 VALIDATION TESTS.....	7
9.0 REFERENCES.....	7
10.0 FLOW CHARTS.....	8

15 March 1963

- 1 -

TM-(L)-734/026/00

## 1.0 IDENTIFICATION

### 1.1 Title

Simulation Data Generation Control Routine (SDGC)

Ident: KO<sup>4</sup>, Mod. 04

### 1.2 Programmed

12 December 1962, G. A. Madrid, System Development Corporation

### 1.3 Documented

12 March 1963, G. A. Madrid, System Development Corporation

## 2.0 PURPOSE

SDGC is used by SIPSA as a subroutine to initiate the ordered execution of the data generation subroutines pre-scheduled by SIPSA, to update the system time counters, and to pack and record the data outputs from the executed subroutines in the formats requested.

## 3.0 USAGE

### 3.1 Calling Sequence

L	SLJ	4	SDGC
L+1	NORMAL RETURN		

15 March 1963

- 2 -

TM-(L)-734/026/00

### 3.2 Parameters

SDGC obtains its input parameters by extracting the contents from the following locations in SIPSA:

<u>Location</u>	<u>Contents</u>
(SIPSA + 14) SIMPAR.....	A five-word table containing the SIPSA input parameters.
(SIPSA + 152) PASSTIME....	Length of generation in seconds.
(SIPSA + 165) SCHED.....	An 11-word table containing the addresses of the subroutines to be executed in the order of operation.
(SIPSA + 203) TLMODE.....	The telemetry mode specified for SIPSA.

### 3.3 Error Printouts and Operator Action

Two types of errors may occur in SDGC. Their printouts and meaning are as follows:

- a. THE OUTPUT TAPE UNIT IS NOT READY. ENABLE UNIT LISTED BELOW THEN HIT START.

This error occurs if the output tape unit is not ready. The operator must enable the unit and hit start to continue.

- b. TOO MANY WORDS ARE BEING GENERATED. TO IGNORE THE PCT CREATING THE OVERLOAD, SET KEY 2 THEN START.

This error occurs if more than 75 words have been selected for generation in any one pseudo second. If it is desirable to continue without the excess data, set SLJ Key 2 and hit start to continue.

15 March 1963

- 3 -

TM-(L)-734/026/00

### 3.4 Tape Assignments and Usage

The tape assignments are dependent on the units specified on the SIPSA function card (TM-(L)-734/025/00). Unit number 3 is reserved for MTCII output and BCD output from the SIPSA System. Unit number 1 is reserved for the master tape containing the SIPSA System. At the CPDC and STA, tape units 2, 4-12 may be specified as parameters on the SIPSA function card.

### 3.5 Control Card Format

SDGC is referenced by SIPSA when it reads a Data Generation Control Card, after having read a START Card and one or more data request cards. The Data Generation Control Card (GENERATE) has the following format:

GENERATE	P <sub>1</sub>
----------	----------------

<u>Columns</u>	<u>Content</u>	<u>Meaning</u>
1-8	GENERATE	Name of the generation request function.
10-13	P <sub>1</sub>	The number of seconds of data which will be generated for recording on the output tape. If this field is left blank and a Reset Tape is being referenced by SIPSA, data will be generated for the entire pass. Otherwise, this value or the duration will be used, whichever is least. If no Reset Tape is used, this field <u>must</u> not be blank or zero.

Since SIPSA reads this card, the P<sub>1</sub> field is processed in SIPSA. However, when SDGC is referenced, this value (PASSTIME) is extracted from the SIPSA Routine.


15 March 1963

- 4 -

TM-(L)-734/026/00

### 3.6 Input or Output Data

The input data to SDGC originates from the various data generation subroutines being executed. This data is transmitted to SDGC via a relocatable buffer area (SIMBUF, TM-(L)-734/030/00). The first word of this buffer contains the length of the message in the buffer. If the message is from a simulated telemetry computer, this length is complemented. The data in the buffer uses the message formats described in the Bird Buffer Combined Milestone 3 and 4, TM-(L)-834/000/01A.



The output data from SDGC consists of the same data contained in SIMBUF, except that in the case of a transfer tape selection (FS), only words, 1-8, are recorded on the output tape. For a BB Tape, the data from each subroutine on the schedule is accumulated as emanating from a telemetry or tracking computer at a tracking station. Each time the schedule is finished, this accumulated data is recorded in the format into which it has been packed. This packing area (DATA) is internal to SDGC. Its format is as follows:

#### STATION DATA RECORD (40, 48-Bit Words)

<u>6-Bit Character</u>	<u>Content</u>
1-2	0002
3-4	Number of simulated 160-A data words generated for the telemetry computer.



<u>6-Bit Character</u>	<u>Content</u>
5-6	Number of simulated 160-A data words generated for the tracking computer.
9-160	Area containing sequentially packed telemetry messages.
161-312	Area containing sequentially packed tracking messages.
313-320	System time in seconds.

### 3.7 Key Settings

Set SLJ Key 2 if it is desired to continue processing after an error stop caused by error b, Section 3.3.

### 4.0 METHOD

After the initialization request card and one or more data generation request cards are processed by SIPSA, a schedule is set up containing the addresses of the data generation modules that are to provide the simulated data requested. The GENERATE Card, which is read next, causes SIPSA to reference SDGC as a subroutine. SDGC then extracts the parameters necessary for its operation from their location in the SIPSA Control Routine and proceeds to execute, sequentially, the ordered addresses in the schedule. If a transfer tape is being prepared, the System Output Buffer (SIMBUF) containing the message prepared at that execution by the generation subroutine, is recorded on the output tape. This is done after the execution of each subroutine in the schedule until the generation time has expired. If a SIMSTN\* Input Tape (BB) is being prepared, the data from each module is unpacked from

---

\*SIMSTN is the Augmented Tracking Station Simulation Program. Refer to documents TM-(L)-734/015/00 and TM-(L)-734/033/00.

15 March 1963

- 6 -

TM-(L)-734/026/00

SIMBUF and packed sequentially into an area of another buffer (DATA) corresponding to the nature of the message (i.e., tracking or telemetry). This cumulative buffer is then recorded after the execution of all of the generation subroutines on the schedule. Generation continues until the designated duration has been reached.

SDGC will produce either a tracking or vehicle time record for an FS Tape or a data record (Type 2) for a BB Tape. Completion of the generate function returns control to SIPSA, which proceeds to read the next input sequence. If these inputs are more data requests, the generation cycle will be repeated. If they are termination requests, SIPSA will end all operations.

## 5.0 RESTRICTIONS

### 5.1 Minimum Hardware or Machine Components Required

Refer to Section 5.0 of TM-(L)-734/025/00, SIPSA Milestone 11.

### 5.2 Subroutines Required

SIPSA	SUBERR
SEAPA	FIX
SDOR	FLOATBIN
SCGR	STCA
STGR	STCB
SRGR	STCC
SIMBUF	STCD
TAPE	STCE

### 5.3 Limits on Input and Output Data

The input data in SIMBUF is limited to a maximum of 75, 160-A words (12-bit words), and the output data in DATA or SIMBUF is likewise limited to this amount.

15 March 1963

- 7 -

TM-(L)-734/026/00

5.4 Reference Pool Items Set or Used

ST.....Station Number

6.0 TIME REQUIREMENTS

The time required to operate SDGC is in direct relationship to the data being generated, length of pass, and the type of output tape being produced. An estimate of time of operation for the SIPSA System may be found in TM-(L)-734/025/00, SIPSA Milestone 11.

7.0 STORAGE REQUIREMENTS

	<u>No. Registers In Octal</u>	<u>No. Registers In Decimal</u>
Instructions	350	232
Storage	<u>121</u>	<u>81</u>
	471	313

8.0 VALIDATION TESTS

The inputs to the SIPSA System, as described in TM-(L)-734/025/00, SIPSA Milestone 11, were used as validation inputs for SDGC. The output from SDGC on magnetic tape showed that the data was processed in accordance with the design specifications. A complete description of the tests is found in the SIPSA Milestone 11 document.

9.0 REFERENCES

9.1 The Control Routine of the Simulated Input Preparation System for the Augmented SCF Environment at the STA and CPDC (SIPSA), Milestone 11, TM-(L)-734/025/00, System Development Corporation, 15 March 1963.

9.2 Bird Buffer Combined Milestone 3 and 4, TM-(L)-834/000/01A, System Development Corporation, 11 February 1963.

15 March 1963

- 8 -

TM-(L)-734/026/00

9.3     Operating Instructions for the Augmented Tracking Station Simulation Program, SIMSTN, Milestone 7, TM-(L)-734/033/00, System Development Corporation, 20 February 1963.

9.4     Computer Design Specifications for the Simulation of the Augmented SCF Environment at the STA and CPDC, Milestone 4, System Development Corporation, TM-(L)-734/015/01A, 9 January 1963.



10.0    FLOW CHARTS



15 March 1963

- 9 -

TM-(L)-734/026/00

APPENDIX A









15 March 1963

- 10 -  
(Last Page)

TM-(L)-734/026/00



TM-(L)-734/026/00





15 March 1963

TM-(L)-734/026/00

DISTRIBUTION  
(EXTERNAL)

Space Systems Division  
(Contracting Agency)

Maj. C. R. Bond (SSOCD)  
Maj. N. D. LaVally (SSOX)

PIR-E4 (GE-Box 8555)

J.S. Brainard  
R. J. Katucki  
J. D. Selby

6594th Aerospace Test Wing  
(Contracting Agency)

Lt. Col. A. W. Dill (TWRD) (10)  
Lt. Col. M. S. McDowell (TWRU)  
TWACS (20)

PIR-E4 (GE-3198 Chestnut)

J.F. Butler  
C. A. Cummings  
H. D. Gilman

PIR-E1 (Lockheed)

J.A. Boysen  
N. N. Epstein  
W. E. Moorman  
G. F. Taylor  
R. L. Vader  
P. E. Williams

PIR-E4 (GE-Bethesda)

W. L. Massey

PIR-E4 (GE-Box 8661)

F. T. Clark  
J. D. Rogers  
W. R. Weinrich

PIR-E2 (Philco)

J. A. Bean  
J. A. Isaacs  
R. Morrison  
S. M. Stanley

PIR-E5 (Aerospace)

A. Bakst  
J. W. Bengston  
R. V. Bigelow  
R. O. Brandsberg  
L.H. Garcia  
G. J. Hansen  
M. L. Luther  
T. R. Parkin  
E. E. Retzlaff  
R. G. Stephenson  
D. D. Stevenson  
V. White

PIR-E3 (LFE)

D. F. Criley  
K. B. Williams

PIR-E4 (GE-Santa Clara)

D. Alexander

PIR-E8 (Mellonics)

PIR-E4 (GE-Sunnyvale)

J. Farrentine  
N. Kirby

F. Druding

(3)

15 March 1963

TM-(L)-734/026/00

<u>NAME</u>	<u>ROOM</u>
D. Reilly	24121
A. Robinson	24132
M. Rockwell	24086
J. Schroeder	24124
R. Scott	24110
C. Seacat	Sunnyvale
H. Seiden	22126
R. Shapiro	24110
S. Shoel	23007
R. Skelton	22152
N. Speer	24086
E. Stone	24058
M. Sweeney	25026
W. Taber	22101
T. Tennant	27029
J. Thompson	24088
C. Toche	24121
R. Totschek	24120
A. Tucker	22109
A. Vorhaus	24076
M. Weinstock	22131
S. Weems	22109
G. West	Sunnyvale
G. P. West	22116
H. Williams	22110
G. Wilson	24124
M. Winsor	22156
J. Winter	24117
R. Wise	22085
J. Wong	Sunnyvale
C. Zubris	24075
AFCPL (5)	14059

15 March 1963

TM-(L)-734/026/00

DISTRIBUTION  
(INTERNAL)

<u>NAME</u>	<u>ROOM</u>	<u>NAME</u>	<u>ROOM</u>
D. Allfree	24083	J. Haake	22153
J. Aldana	22131	D. Henley	22094
L. Alexander	22134	C. Hill	22101
N. Alperin	22153	J. Hillhouse	22078
E. Armstrong	24123	H. Holzman	24065
		G. Hudson	24126
C. Becerra	24082		
D. Biggar	24118	R. Johnson	22125
R. Bilek	23007		
L. Brenton	24103	P. Kastama	22076
B. Burke	24086	M. Katz	25014
R. Burke	22158	F. Kayser	24109
R. Busch	22068	J. Keddy	24105
C. Bustya	22134	D. Key	23013
		R. Keyes	24073
M. Champaign	22152	J. Kneemeyer	22088
C. Chiodini	24091	R. Knight	22119
B. Ciaccia	24082	L. Kolbo	22155
R. Clements	22109		
B. Cline	24127	J. Laughlin	24073
J. Cogley	22156	J. LaVine	24093
L. Conger	24088	H. Lewis	23010
P. Cooley	24086	J. Little	24088
D. Crum	24105	F. Long	22156
		J. Lytton	24077
L. DeCuir	24053		
W. Derango	24082	G. Madrid	22081
G. Dexter	25016	G. Mahon	24089
R. Disse	23014	J. Marioni	24076
G. Dobbs	22116	R. Marshall	22160
W. Dobrusky	24065	W. Martin	24127
R. Dugas	22125	J. McKeown	23013
		J. Milanese	22155
R. Ellis	22131	J. Munson	22087
R. Ericksen	22113	G. Myers	22095
H. Feldstein	24128	P. Nelson	24075
C. Francis	25013	J. Ng	22077
M. Franks	24122	L. Ngou	24127
R. Frey	22078		
L. Friedman	22122	M. Olson	22161
S. Gardner	25026	L. Padgett	24110
V. Gergen	25014	E. Patin	Sunnyvale
I. Greenwald	22094	D. Persico	24083
		T. Polk	24113

UNCLASSIFIED

System Development Corporation,  
Santa Monica, California  
1604 SIMULATION PROGRAM DESCRIPTIONS  
MILESTONE 11 SIMULATED DATA GENERATION  
CONTROL ROUTINE (SDGC).  
Scientific rept., TM(L)-734/026/00, by  
G. A. Madrid. 15 March 1963, 10p.,  
4 refs.  
(Contract AF 19(628)-1648, Space System  
Division Program, for Space Systems  
Division, AFSC)

Unclassified report

DESCRIPTORS: Programming (Computers).  
Satellite Networks.

UNCLASSIFIED

---

Reports that SDGC (Simulation Data  
Generation Control Routine) is used  
by the ordered execution of the data  
generation subroutines pre-scheduled  
by SIPSA, to update the system time  
counters, and to pack outputs from the  
executed subroutines in the formats  
requested.

UNCLASSIFIED

UNCLASSIFIED